

**NAME**

CURLOPT\_APPEND – enable appending to the remote file

**SYNOPSIS**

```
#include <curl/curl.h>
```

```
CURLcode curl_easy_setopt(CURL *handle, CURLOPT_APPEND, long append);
```

**DESCRIPTION**

A long parameter set to 1 tells the library to append to the remote file instead of overwrite it. This is only useful when uploading to an FTP site.

**DEFAULT**

0 (disabled)

**PROTOCOLS**

FTP

**EXAMPLE**

```
CURL *curl = curl_easy_init();
if(curl) {

    curl_easy_setopt(curl, CURLOPT_URL, "ftp://example.com/dir/to/newfile");
    curl_easy_setopt(curl, CURLOPT_UPLOAD, 1L);
    curl_easy_setopt(curl, CURLOPT_APPEND, 1L);

    curl_easy_perform(curl);
}
```

**AVAILABILITY**

This option was known as CURLOPT\_FTPAPPEND up to 7.16.4

**RETURN VALUE**

Returns CURLE\_OK if the option is supported, and CURLE\_UNKNOWN\_OPTION if not.

**SEE ALSO**

CURLOPT\_DIRLISTONLY(3), CURLOPT\_RESUME\_FROM(3), CURLOPT\_UPLOAD(3),