

NAME

CURLOPT_HTTP200ALIASES – specify alternative matches for HTTP 200 OK

SYNOPSIS

```
#include <curl/curl.h>
```

```
CURLcode curl_easy_setopt(CURL *handle, CURLOPT_HTTP200ALIASES,  
                           struct curl_slist *aliases);
```

DESCRIPTION

Pass a pointer to a linked list of *aliases* to be treated as valid HTTP 200 responses. Some servers respond with a custom header response line. For example, SHOUTcast servers respond with "ICY 200 OK". Also some very old Icecast 1.3.x servers will respond like that for certain user agent headers or in absence of such. By including this string in your list of aliases, the response will be treated as a valid HTTP header line such as "HTTP/1.0 200 OK".

The linked list should be a fully valid list of struct curl_slist structs, and be properly filled in. Use *curl_slist_append(3)* to create the list and *curl_slist_free_all(3)* to clean up an entire list.

The alias itself is not parsed for any version strings. The protocol is assumed to match HTTP 1.0 when an alias match.

DEFAULT

NULL

PROTOCOLS

HTTP

EXAMPLE

TODO

AVAILABILITY

Added in 7.10.3

RETURN VALUE

Returns CURLE_OK if HTTP is supported, and CURLE_UNKNOWN_OPTION if not.

SEE ALSO

CURLOPT_HTTP_VERSION(3),