

The `luamml` package ^{*}

Marcel Krüger

June 25, 2025

1 Use case

When generating output for the web or tagged output, mathematical content should often be represented as MathML. This uses Lua \TeX callbacks to automatically attempt to convert Lua \TeX math mode output into MathML.

2 Usage

The `luamml` package is designed to be used in automated ways by other packages and usually should not be invoked directly by the end user.

Typically you will use it through `latex-lab-math`. See the `latex-lab-math` documentation for user instructions.

If you want to use `luamml` in another context, the `luamml` package can be included directly, followed by enclosing blocks which should generate files with `luamml_begin_single_file:` and `luamml_end_single_file:`. The filename can be set with `luamml_set_filename:n`.

3 Improving MathML conversion

When using constructs which do not automatically get converted in acceptable form, conversion hints can be provided with `luamml_annotate:en`. This allows to provide a replacement MathML structure in Lua table form, for example

```
\luamml_annotate:en {
  nucleus = true,
  core = {[0] = 'mi', 'TeX'},
}{
  \hbox{\TeX}
}
```

produces a `<mi>TeX</mi>` element in the output instead of trying to import \TeX as a mathematical expression.

It is possible to add a structure around the construct, stash that structure and then to tell `luamml_annotate:en` to insert it later inside the math. For this the keys `struct` (which takes a label as argument) or `structnum` (which takes a structure number) can be used. For example

^{*}This document corresponds to `luamml` v0.6.0, dated 2025-06-25.

```

$a = b \quad
\tagstructbegin{tag=mtext,stash}\tagmcbegin{}
\luamml_annotate:en{nucleus=true,structnum=\tag_get:n{struct_num}}
{\mbox{some~text~with~\emph{structure}}}}
\tagmcbend\tagstructend
$

```

Such a construction should check that the flag for structure elements has actually been set to avoid orphaned structures if the stashed structure is ignored.

More about the table structure is explained in an appendix.

4 Features & Limitations

Currently all mathematical expressions which purely contain Unicode encoded math mode material without embedded non-math should get converted successfully. Usage with non-Unicode math (T_EX's 8-bit math fonts) is highly experimental and undocumented. Any attempt to build complicated structures by embedding arbitrary T_EX code in the middle of math mode needs to have a MathML replacement specified. We try to automate more cases in the future.

A Luamml's representation of XML and MathML

In the following I assume basic familiarity with both LuaT_EX's representation of math nodes and MathML.

A.1 Representation of XML elements

In many places, luamml passes around XML elements. Every element is represented by a Lua table. Element 0 must always be present and is a string representing the tag name. The positive integer elements of the table represent child elements (either strings for direct text content or nested tables for nested elements). All string members which do not start with a colon are attributes, whose value is the result of applying `tostring` to the field value. This implies that these values should almost always be strings, except that the value 0 (since it never needs a unit) can often be set as a number. For example the XML document

```

<math block="display">
  <mn>0</mn>
  <mo> &lt; </mo>
  <mi mathvariant="normal">x</mi>
</math>

```

would be represented by the Lua table

```

{[0] = "math", block="display",
  {[0] = "mn", "0"},
  {[0] = "mo", "<"},
  {[0] = "mi", mathvariant="normal", "x"}
}

```

A.2 Expression cores

MathML knows the concept of “embellished operators”: “The precise definition of an “embellished operator” is:

- an `<mo>` element;
- or one of the elements `<msub>`, `<msup>`, `<msubsup>`, `<munder>`, `<mover>`, `<munderover>`, `<mmultiscripts>`, `<mfrac>`, or `<semantics>` (§ 5.1 Annotation Framework), whose first argument exists and is an embellished operator;
- or one of the elements `<mstyle>`, `<mphantom>`, or `<mpadded>`, such that an `mrow` containing the same arguments would be an embellished operator;
- or an `<maction>` element whose selected sub-expression exists and is an embellished operator;
- or an `<mrow>` whose arguments consist (in any order) of one embellished operator and zero or more space-like elements.

For every embellished operator, MathML calls the `<mo>` element defining the embellished operator the “core” of the embellished operator.

Luamml makes this slightly more general: Every expression is represented by a pair of two elements: The expression and its core. The core is always a `<mo>`, `<mi>`, or `<mn>`, `nil` or `s` special marker for space like elements.

If and only if the element is an embellished operator the core is a `<mo>` element representing the core of the embellished operator. The core is a `<mi>` or a `<mn>` element if and only if the element would be an embellished operator with this core if this element were a `<mo>` element. The core is the special space like marker for space like elements. Otherwise the core is `nil`.

A.3 Translation of math noads

A math list can contain the following node types: noad, fence, fraction, radical, accent, style, choice, ins, mark, adjust, boundary, whatsit, penalty, disc, glue, and kern. The “noads”

A.3.1 Translation of kernel noads

The math noads of this list contain nested kernel noads. So in the first step, we look into how kernel nodes are translated to math nodes.

math_char kernel noads First the family and character value in the `math_char` are used to lookup the Unicode character value of this `math_char`. (For `unicode-math`, this is usually just the character value. Legacy maths has to be remapped based on the family.) Then there are two cases: The digits 0 to 9 are mapped to `<mn>` elements, everything else becomes a `<mi>` element with `mathvariant` set to `normal`. (The `mathvariant` value might get suppressed if the character defaults to `mathvariant normal`.) In either case, the `tex:family` attribute is set to the family number if it’s not 0.

The core is always set to the expression itself. E.g. the `math_char` kernel noad `\fam3 a` would become (assuming no remapping for this family)

```
{[0] = 'mi',
  mathvariant = 'normal',
  ["tex:family"] = 3,
  "a"
}
```

A.3.2 sub_box kernel noads

I am open to suggestions how to convert them properly.

A.3.3 sub_mlist kernel noads

The inner list is converted as a `<mrow>` element, with the core being the core of the `<mrow>` element. See the rules for this later.

A.3.4 delim kernel noads

If the `small_char` is zero, these get converted as space like elements of the form

```
{[0] = 'mspace',
  width = '1.196pt',
}
```

where 1.196 is replaced by the current value of `\nulldelimiterspace` converted to bp.

Otherwise the same rules as for `math_char` apply, except that instead of `mi` or `<mn>` elements, no elements are generated, `mathvariant` is never set, `stretchy` is set to `true` if the operator is not on the list of default stretchy operators in the MathML specification and `lspace` and `rspace` attributes are set to zero.

A.3.5 acc kernel noads

Depending on the surrounding element containing the `acc` kernel noad, it is either stretchy or not. If it's stretchy, the same rules as for `delim` apply, except that `lspace` and `rspace` are not set. Otherwise the `stretchy` attribute is set to `false` if the operator is on the list of default stretchy operators.

B Package Implementation

B.1 Initialization

```
1 <@@=luamml>
2 <*luatex>
3 \ProvidesExplPackage {luamml} {2025-06-25} {0.6.0}
4   {Automatically generate presentational MathML from LuaTeX math expressions}
5 </luatex>
6 <*pdfTeX>
7 \ProvidesExplPackage {luamml-pdf} {2025-06-25} {0.6.0}
8   {MathML generation for Lua pdfLaTeX}
9 </pdfTeX>
```

B.2 Initialization

These variables have to appear before the Lua module is loaded and will be used to communicate information to the callback.

Here `\tracingmathml` does not use an `expl3` name since it is not intended for programming use but only as a debugging helper for the user. The other variables are internal, but we provide public interfaces for setting them later.

```
10 \int_new:N \l__luamml_flag_int
```

This integer decides if the xml uses pretty indentation if output to a file or to the terminal. It is used in `luamml-tex.lua` with a bitwise operation. Indentation in files is activated if bit 0 is set. Indentation in the log is activated if bit 1 is set. Bit 2 sets indentation for code added with the `\luamml_register_output_hook:N`. Bit 3 sets indentation for MathML written as stream to the PDF with `\luamml_get_last_mathml_stream:e`.

```
11 \int_new:N \l__luamml_pretty_int
12 \langle\luatex\rangle\tl_new:N \l__luamml_filename_tl
13 \tl_new:N \l__luamml_root_tl
14 \tl_set:Nn \l__luamml_root_tl { mrow }
15 \tl_new:N \l__luamml_label_tl
16 \langle\pdf\langle\luatex\rangle\int_new:N \g__luamml_formula_id_int
17 \langle\luatex\rangle\int_new:N \tracingmathml
18
19 \int_set:Nn \l__luamml_pretty_int { 1 }
```

Currently we disable flattening in LuaTeX to avoid annotations getting lost. We will consider later if flattening needs to be reenabled depending, but then with a different implementation.

```
20 \langle\luatex\rangle\tex_mathflattenmode:D = 0 \scan_stop:
```

Now we can load the Lua module which defines the callback. Of course until `pdfTeX` starts implementing `\directlua` this is only done in LuaTeX.

```
21 \langle\luatex\rangle\lua_now:n { require'luamml-tex' }
```

B.3 Hook

We also call a hook with arguments at the end of every MathML conversion with the result. Currently only implemented in LuaTeX since it immediately provides the output. TODO: the `latex-lab-math` code registers its own function and so effectively kills the hook here. This should be sorted ...

```
22 \langle\luatex\rangle
23 \hook_new_with_args:nn { luamml / converted } { 1 }
24
25 \cs_new_protected:Npn \__luamml_output_hook:n {
26   \hook_use:nnw { luamml / converted } { 1 }
27 }
28 \__luamml_register_output_hook:N \__luamml_output_hook:n
29 \langle\luatex\rangle
```

B.4 Flags

The most important interface is for setting the flag which controls how the formulas should be converted.

`\luamml_process:` Consider the current formula to be a complete, free-standing mathematical expression which should be converted to MathML. Additionally, the formula is also saved in the `start_math` node as with `\luamml_save:`.

```
30 \cs_new_protected:Npn \luamml_process: {
31   \tl_set:Nn \l__luamml_label_tl {}
32   \int_set:Nn \l__luamml_flag_int { 3 }
33 }
```

Temporarily for compatibility

```
34 \cs_set_eq:NN \luamml_flag_process: \luamml_process:
```

(End of definition for `\luamml_process:`. This function is documented on page ??.)

`__luamml_maybe_structelem:` A internal helper which can be added to a tag to preserve the external state of the `structelem` flag.

```
35 \cs_new:Npn \__luamml_maybe_structelem: {
36   (
37     8 * \int_mod:nn {
38       \int_div_truncate:nn { \l__luamml_flag_int } {8}
39     } {2}
40   ) +
41 }
```

(End of definition for `__luamml_maybe_structelem:`.)

`__luamml_style_to_num:N`

```
42 \cs_new:Npn \__luamml_style_to_num:N #1 {
43   \langle luatex \rangle 32 * #1
44   \langle *pdfTeX \rangle
45   \token_case_meaning:NnF #1 {
46     \displaystyle {0}
47     \textstyle {32}
48     \scriptstyle {64}
49     \scriptscriptstyle {96}
50   } {
51     \InvalidMathstyle
52   }
53   \langle /pdfTeX \rangle
54 }
```

(End of definition for `__luamml_style_to_num:N`.)

`\luamml_save:n` Convert the current formula but only save it's representation in the math node without emitting it as a complete formula. This is useful when the expression forms part of a bigger formula and will be integrated into it's MathML tables later by special code. It optionally accepts three parameters: A label, one math style command (`\displaystyle`, `\textstyle`, etc.) which is the implicit math style (so the style which the surrounding code expects this style to have) and a name for the root element (defaults to `mrow`). If the root element name is `mrow`, it will get suppressed in some cases.

```
55 \cs_new_protected:Npn \luamml_save:n #1 {
56   \tl_set:Nn \l__luamml_label_tl {#1}
57   \int_set:Nn \l__luamml_flag_int { \__luamml_maybe_structelem: 1 }
58 }
59 \cs_new_protected:Npn \luamml_save:nN #1#2 {
```

```

60 \tl_set:Nn \l__luamml_label_tl {#1}
61 \int_set:Nn \l__luamml_flag_int { \__luamml_maybe_structelem: 17 + \__luamml_style_to_num:N }
62 }
63 \cs_new_protected:Npn \luamml_save:nn #1 {
64 \tl_set:Nn \l__luamml_label_tl {#1}
65 \int_set:Nn \l__luamml_flag_int { \__luamml_maybe_structelem: 5 }
66 \tl_set:Nn \l__luamml_root_tl
67 }
68 \cs_new_protected:Npn \luamml_save:nNn #1#2 {
69 \tl_set:Nn \l__luamml_label_tl {#1}
70 \int_set:Nn \l__luamml_flag_int { \__luamml_maybe_structelem: 21 + \__luamml_style_to_num:N }
71 \tl_set:Nn \l__luamml_root_tl
72 }

```

Temporarily for compatibility

```

73 \cs_set_eq:NN \luamml_flag_save:n \luamml_save:n
74 \cs_set_eq:NN \luamml_flag_save:nN \luamml_save:nN
75 \cs_set_eq:NN \luamml_flag_save:nn \luamml_save:nn
76 \cs_set_eq:NN \luamml_flag_save:nNn \luamml_save:nNn

```

(End of definition for \luamml_save:n and others. These functions are documented on page ??.)

`\luamml_ignore:` Completely ignore the math mode material.

```

77 \cs_new_protected:Npn \luamml_ignore: {
78 \int_set:Nn \l__luamml_flag_int { 0 }
79 }

```

Temporarily for compatibility

```

80 \cs_set_eq:NN \luamml_flag_ignore: \luamml_ignore:

```

(End of definition for \luamml_ignore:. This function is documented on page ??.)

`\luamml_structelem:` Like `\luamml_process:`, but additionally adds PDF structure elements. This only works in Lua \TeX and requires that the `tagpdf` package has been loaded *before* `luamml`.

```

81 \langle*luatex\rangle
82 \cs_new_protected:Npn \luamml_structelem: {
83 \tl_set:Nn \l__luamml_label_tl {}
84 \int_set:Nn \l__luamml_flag_int { 11 }
85 }

```

Temporarily for compatibility

```

86 \cs_set_eq:NN \luamml_flag_structelem: \luamml_structelem:
87 \langle/luatex\rangle

```

(End of definition for \luamml_structelem:. This function is documented on page ??.)

`\luamml_set_filename:n` Allows to set a filename to which the generated MathML gets written. Previous content from the file will get overwritten. This includes results written by a previous formula. Therefore this has to be called separately for every formula or it must expand to different values to be useful. The value is fully expanded when the file is written.

Only complete formulas get written into files (so formulas where `\luamml_process:` or `\luamml_structelem:` are in effect).

Only implemented in Lua \TeX , in pdf \TeX the arguments for `pdfmml` determine the output location.

```

88 \langle*luatex\rangle

```

```

89 \cs_new_protected:Npn \luamml_set_filename:n {
90   \tl_set:Nn \l__luamml_filename_tl
91 }
92 </luatex>

```

(End of definition for `\luamml_set_filename:n`. This function is documented on page ??.)

`\luamml_begin_single_file:` Everything between these two commands gets written into the same XML file. The
`\luamml_end_single_file:` filename is expanded when `\luamml_begin_single_file:` gets executed.
 (Implemented in Lua)

(End of definition for `\luamml_begin_single_file:` and `\luamml_end_single_file:`. These functions are documented on page ??.)

By default, the flag is set to assume complete formulas.

```

93 \luamml_process:

```

B.5 Annotations

These are implemented very differently depending on the engine, but the interface should be the same.

B.5.1 LuaTeX

```

94 <*luatex>

```

`\luamml_annotate:nen` A simple annotation scheme: The first argument is the number of top level noads to be
`\luamml_annotate:en` annotated, the second parameter the annotation and the third parameter the actual list
 of math tokens. The first argument can be omitted to let LuaTeX determine the number
 itself.

Passing the first parameter explicitly is useful for any annotations which should be compatible with future pdfTeX versions of this functionality.

```

95 \cs_new_protected:Npn \luamml_annotate:nen #1#2#3 {
96   \__luamml_annotate_begin:
97   #3
98   \__luamml_annotate_end:we \tex_numexpr:D #1 \scan_stop: {#2}
99 }
100
101 \cs_new_protected:Npn \luamml_annotate:en #1#2 {
102   \__luamml_annotate_begin:
103   #2
104   \__luamml_annotate_end:e {#1}
105 }

```

(End of definition for `\luamml_annotate:nen` and `\luamml_annotate:en`. These functions are documented on page ??.)

`\luamml_attribute:nnn` Set a MathML attribute on a MathML node.

```

\luamml_attribute_core:nnn
106 \cs_new_protected:Npn \luamml_attribute:een #1#2#3 {
107   \__luamml_annotate_begin:
108   #3
109   \__luamml_annotate_attribute_end:wee {#1} {#2}
110 }
111
112 \cs_new_protected:Npn \luamml_attribute_core:een #1#2#3 {

```



```

113 \__luamml_annotate_begin:
114     #3
115     \__luamml_annotate_attribute_end:wee core {#1} {#2}
116 }

```

(End of definition for `\luamml_attribute:nnn` and `\luamml_attribute_core:nnn`. These functions are documented on page ??.)

```

117 </luatex>

```

B.5.2 pdfTeX

```

118 <*pdfTeX>

```

`__luamml_pdf_showlists:` Here and in many other locations the pdfTeX implementation is based on `\showlists`, so we define an internal wrapper which sets all relevant parameters.

```

119 \cs_if_exist:NTF \showstream {
120     \iow_new:N \l__luamml_pdf_stream
121     \iow_open:Nn \l__luamml_pdf_stream { \jobname .tml }
122     \cs_new_protected:Npn \__luamml_pdf_showlists: {
123         \group_begin:
124             \int_set:Nn \tex_showboxdepth:D { \c_max_int }
125             \int_set:Nn \tex_showboxbreadth:D { \c_max_int }
126             \showstream = \l__luamml_pdf_stream
127             \tex_showlists:D
128         \group_end:
129     }
130 } {
131     \cs_set_eq:NN \l__luamml_pdf_stream \c_log_iow
132     \cs_set_eq:NN \__luamml_pdf_set_showstream: \scan_stop:
133     \cs_new_protected:Npn \__luamml_pdf_showlists: {
134         \group_begin:
135             \int_set:Nn \l_tmpa_int { \tex_interactionmode:D }
136             \int_set:Nn \tex_interactionmode:D { 0 }
137             \int_set:Nn \tex_showboxdepth:D { \c_max_int }
138             \int_set:Nn \tex_showboxbreadth:D { \c_max_int }
139             \tex_showlists:D
140             \int_set:Nn \tex_interactionmode:D { \l_tmpa_int }
141         \group_end:
142     }
143 }

```

(End of definition for `__luamml_pdf_showlists:.`)

`\luamml_annotate:nen` Now we can define the annotation commands for pdfTeX.

```

\luamml_annotate:en
144 \cs_generate_variant:Nn \tl_to_str:n { e }
145 \int_new:N \g__luamml_annotation_id_int
146 \cs_new_protected:Npn \luamml_annotate:nen #1#2#3 {
147     \int_gincr:N \g__luamml_annotation_id_int
148     \iow_shipout_x:Nx \l__luamml_pdf_stream {
149         LUAMML_MARK_REF:
150         \int_use:N \g__luamml_annotation_id_int
151         :
152     }
153     \iow_now:Nx \l__luamml_pdf_stream {

```

```

154 LUAMML_MARK:
155 \int_use:N \g__luamml_annotation_id_int
156 :
157 count = \int_eval:n {#1},
158 #2
159 \iow_newline:
160 LUAMML_MARK_END
161 }
162 #3
163 }
164 \cs_new_protected:Npn \luamml_annotate:en #1#2 {
165 \int_gincr:N \g__luamml_annotation_id_int
166 \iow_shipout_x:Nx \l__luamml_pdf_stream {
167 LUAMML_MARK_REF:
168 \int_use:N \g__luamml_annotation_id_int
169 :
170 }
171 \iow_now:Nx \l__luamml_pdf_stream {
172 LUAMML_MARK:
173 \int_use:N \g__luamml_annotation_id_int
174 :
175 count = data.count[\int_use:N \g__luamml_annotation_id_int],
176 #1
177 \iow_newline:
178 LUAMML_MARK_END
179 }
180 \use:x {
181 \iow_now:Nn \l__luamml_pdf_stream {
182 LUAMML_COUNT:
183 \int_use:N \g__luamml_annotation_id_int
184 }
185 \__luamml_pdf_showlists:
186 \exp_not:n {#2}
187 \iow_now:Nn \l__luamml_pdf_stream {
188 LUAMML_COUNT_END:
189 \int_use:N \g__luamml_annotation_id_int
190 }
191 \__luamml_pdf_showlists:
192 }
193 }

```

(End of definition for \luamml_annotate:nen and \luamml_annotate:en. These functions are documented on page ??.)

```
194 </pdfTeX>
```

B.6 Trigger for specific formula

This only applies for pdf \TeX since in Lua \TeX everything is controlled by the callback, but for compatibility the function is defined anyway.

`\luamml_pdf_write:` We could accept parameters for the flag and tag here, but for compatibility with Lua \TeX they are passed in macros instead.

```

195 <*pdfTeX>
196 \cs_new_protected:Npn \luamml_pdf_write: {

```

```

197 \int_gincr:N \g__luamml_formula_id_int
198 \iow_now:Nx \l__luamml_pdf_stream {
199   LUAMML_FORMULA_BEGIN:
200   \int_use:N \g__luamml_formula_id_int
201   :
202   \int_use:N \l__luamml_flag_int
203   :
204   \l__luamml_root_tl
205   :
206   \l__luamml_label_tl
207 }
208 \__luamml_pdf_showlists:
209 \iow_now:Nx \l__luamml_pdf_stream {
210   LUAMML_FORMULA_END
211 }
212 }
213 </pdfTeX>
214 <luaTeX>\cs_new_eq:NN \luamml_pdf_write: \scan_stop:

```

(End of definition for \luamml_pdf_write:. This function is documented on page ??.)

B.7 Further helpers

`\RegisterFamilyMapping` The Lua version of this is defined in the Lua module.

```

215 <*pdfTeX>
216 \NewDocumentCommand \RegisterFamilyMapping {m m} {
217   \iow_now:Nx \l__luamml_pdf_stream {
218     LUAMML_INSTRUCTION:REGISTER_MAPPING: \int_use:N #1 : #2
219   }
220 }
221 </pdfTeX>

```

(End of definition for \RegisterFamilyMapping. This function is documented on page ??.)

B.8 Sockets

In various places `luamml` has to add code to kernel commands. This is done through sockets which are predeclared in `ltagging`.

B.8.1 Save sockets

These sockets are wrappers around the `\luamml_save:...` commands They should be provided until 2025-06-01

```

222 \str_if_exist:cF { l__socket_tagsupport/math/luamml/save/nn_plug_str }
223 {
224   \NewSocket{tagsupport/math/luamml/save/nn}{1}
225   \AssignSocketPlug{tagsupport/math/luamml/save/nn}{noop}
226   \NewSocket{tagsupport/math/luamml/save/nNn}{1}
227   \AssignSocketPlug{tagsupport/math/luamml/save/nNn}{noop}
228 }

```

```

229 \NewSocketPlug{tagssupport/math/luamml/save/nNn}{luamml}
230 {
231   \luamml_save:nNn #1
232 }
233 \AssignSocketPlug{tagssupport/math/luamml/save/nNn}{luamml}
234 \NewSocketPlug{tagssupport/math/luamml/save/nn}{luamml}
235 {
236   \luamml_save:nn #1
237 }
238 \AssignSocketPlug{tagssupport/math/luamml/save/nn}{luamml}

```

B.8.2 sockets to annotate content

```

239 \str_if_exist:cF { l__socket_tagssupport/math/luamml/annotate/false_plug_str }
240 {
241   \NewSocket{tagssupport/math/luamml/annotate/false}{2}
242   \NewSocketPlug{tagssupport/math/luamml/annotate/false}{default}{#2}
243   \AssignSocketPlug{tagssupport/math/luamml/annotate/false}{default}
244 }
245 <*luatex>
246 \NewSocketPlug{tagssupport/math/luamml/annotate/false}{luamml}
247 {
248   \luamml_annotate:en { core = false }
249   {
250     #2
251   }
252 }
253 \AssignSocketPlug{tagssupport/math/luamml/annotate/false}{luamml}
254 </luatex>

```

B.8.3 socket plugs for the array package

The socket declaration can go with the 2025-06-01 release

```

255 \str_if_exist:cF { l__socket_tagssupport/math/luamml/array/finalize_plug_str }
256 {
257   \NewSocket{tagssupport/math/luamml/array/save}{0}
258   \NewSocket{tagssupport/math/luamml/array/finalize}{0}
259   \NewSocket{tagssupport/math/luamml/array/initcol}{0}
260   \NewSocket{tagssupport/math/luamml/array/finalizecol}{1}
261   \AssignSocketPlug{tagssupport/math/luamml/array/finalizecol}{noop}
262 }

```

The luamml support makes only sense with luatex.

```

263 <*luatex>
264 \AddToHook{package/array/after}{\lua_now:n { require'luamml-array' }}

```

t/math/luamml/array/save (*plug*) The socket of this plug is used in `\endarray`.

```

265 \NewSocketPlug{tagssupport/math/luamml/array/save}{luamml}
266 {
267   \__luamml_array_save_array:
268 }

```

th/luamml/array/finalize (*plug*) This socket of this plug is used in `\endarray`.

```

269 \NewSocketPlug{tagssupport/math/luamml/array/finalize}{luamml}
270 {

```

```

271 \mode_if_math:T { \__luamml_array_finalize_array: }
272 }

```

math/luamml/array/initcol (*plug*) The socket of this plug is used in \@classz.

```

273 \NewSocketPlug{tagssupport/math/luamml/array/initcol}{luamml}
274 {
275   \__luamml_array_init_col:
276 }

```

luamml/array/finalizecol (*plug*) The socket of this plug is used in \@classz.

```

277 \NewSocketPlug{tagssupport/math/luamml/array/finalizecol}{luamml}
278 {
279   \__luamml_array_finalize_col:w #1~
280 }

```

```

281 \AssignSocketPlug{tagssupport/math/luamml/array/save}{luamml}
282 \AssignSocketPlug{tagssupport/math/luamml/array/finalize}{luamml}
283 \AssignSocketPlug{tagssupport/math/luamml/array/initcol}{luamml}
284 \AssignSocketPlug{tagssupport/math/luamml/array/finalizecol}{luamml}
285 \</luatex>

```

B.8.4 amsmath alignments

This socket is used at the end of alignment cells and adds the content to the current row.

```

286 \str_if_exist:cF { l__socket_tagssupport/math/luamml/mtable/finalizecol_plug_str }
287 {
288   \NewSocket{tagssupport/math/luamml/mtable/finalizecol}{1}
289 }
290 \< *luatex>
291 \NewSocketPlug{tagssupport/math/luamml/mtable/finalizecol}{luamml}
292 {
293   \use:c{__luamml_amsmath_add_#1_to_row:}
294 }
295 \AssignSocketPlug{tagssupport/math/luamml/mtable/finalizecol}{luamml}
296
297 \</luatex>

```

These sockets save an inner table

```

298 \str_if_exist:cF { l__socket_tagssupport/math/luamml/mtable/innertable/save_plug_str }
299 {
300   \NewSocket{tagssupport/math/luamml/mtable/innertable/save}{0}
301   \NewSocket{tagssupport/math/luamml/mtable/smallmatrix/save}{0}
302   \NewSocket{tagssupport/math/luamml/mtable/innertable/finalize}{0}
303 }
304 \< *luatex>
305 \NewSocketPlug{tagssupport/math/luamml/mtable/innertable/save}{luamml}
306 {
307   \__luamml_amsmath_save_inner_table:n \@currenenvir
308 }
309 \AssignSocketPlug{tagssupport/math/luamml/mtable/innertable/save}{luamml}
310 \NewSocketPlug{tagssupport/math/luamml/mtable/smallmatrix/save}{luamml}
311 {
312   \__luamml_amsmath_save_smallmatrix:

```

```

313 }
314 \AssignSocketPlug{tagssupport/math/luamml/mtable/smallmatrix/save}{luamml}
315 \NewSocketPlug{tagssupport/math/luamml/mtable/innertable/finalize}{luamml}
316 {
317   \_luamml_amsmath_finalize_inner_table:
318 }
319 \AssignSocketPlug{tagssupport/math/luamml/mtable/innertable/finalize}{luamml}
320 </luatex>

```

This socket finalize the mtable in alignments like align or gather. It takes an argument, the environment. It should be used normally with \UseExpandableTaggingSocket.

```

321 \str_if_exist:cF { l__socket_tagssupport/math/luamml/mtable/finalize_plug_str }
322 {
323   \NewSocket{tagssupport/math/luamml/mtable/finalize}{1}
324   \AssignSocketPlug{tagssupport/math/luamml/mtable/finalize}{noop}
325 }
326 <*luatex>
327 \NewSocketPlug{tagssupport/math/luamml/mtable/finalize}{luamml}
328 {
329   \_luamml_amsmath_finalize_table:n {#1}
330 }
331 \AssignSocketPlug{tagssupport/math/luamml/mtable/finalize}{luamml}
332 </luatex>

```

This socket adds attributes for the alignment in multiline. It takes an argument, the alignment.

```

333 \str_if_exist:cF { l__socket_tagssupport/math/luamml/mtable/aligncol_plug_str }
334 {
335   \NewSocket{tagssupport/math/luamml/mtable/aligncol}{1}
336   \AssignSocketPlug{tagssupport/math/luamml/mtable/aligncol}{noop}
337 }
338 <*luatex>
339 \NewSocketPlug{tagssupport/math/luamml/mtable/aligncol}{luamml}
340 {
341   \_luamml_amsmath_set_row_columnalign:n {#1}
342 }
343 \AssignSocketPlug{tagssupport/math/luamml/mtable/aligncol}{luamml}
344 </luatex>

```

B.8.5 Tags and labels

These sockets save and set tags and labels in alignments.

```

345 \str_if_exist:cF { l__socket_tagssupport/math/luamml/mtable/tag/save_plug_str }
346 {
347   \NewSocket{tagssupport/math/luamml/mtable/tag/save}{0}
348   \NewSocket{tagssupport/math/luamml/mtable/tag/set}{0}
349 }
350 <*luatex>
351 \int_new:N \l__luamml_amsmath_tag_struct_num_int
352 \NewSocketPlug{tagssupport/math/luamml/mtable/tag/save}{luamml}
353 {
354   \_luamml_amsmath_save_tag_with_struct_elem:N \l__luamml_amsmath_tag_struct_num_int
355 }

```

```

356 \AssignSocketPlug{tag-support/math/luamml/mtable/tag/save}{luamml}
357 \NewSocketPlug{tag-support/math/luamml/mtable/tag/set}{luamml}
358 {
359   \_luamml_amsmath_set_tag:
360 }
361 \AssignSocketPlug{tag-support/math/luamml/mtable/tag/set}{luamml}
362
363 </luatex>

```

If math structure elements are created the Lbl-structure of a tag must be moved inside the math structure, typically as an additional column in an mtable with an intent :equation-label or :no-equation-label.

The luamml-code handles this by stashing the Lbl-structure, storing the structure number in an array and reusing it once it creates the math structure elements.

This should only be done for specific environments, we define a constant to test:

```

364 \str_if_exist:cF { l__socket_tag-support/math/display/tag/begin_plug_str }
365 {
366   \NewSocket{tag-support/math/display/tag/begin}{0}
367   \NewSocket{tag-support/math/display/tag/end}{0}
368 }
369 <*luatex>
370 \clist_map_inline:nn
371 {
372   align,
373   align*,
374   alignat,
375   alignat*,
376   xalignat,
377   xalignat*,

```

there is never a tag/label in xxalignat, so does it make sense to add a label column? Left out for now.

```

378   %xxalignat,
379   flalign,
380   flalign*,
381   gather,
382   gather*,

```

equation and multiline have at most one tag, so we do not use a label column but rely on the external Lbl for now.

```

383   %multiline, % NO
384   %multiline*, % NO
385   %equation, % NO
386   %equation*, % NO

```

split has never a numbering so is ignored

```

387   %split, % NO
388 }
389 {\tl_const:cn { c__luamml_label_#1_tl}{}}
390 \NewSocketPlug{tag-support/math/display/tag/begin}{luamml}
391 {
392   \tag_mc_end:
393   \bool_lazy_and:nnT
394   { \tl_if_exist_p:c { c__luamml_label_ \@currentenvir _tl } }

```

```

395 { \int_if_odd_p:n { \int_div_truncate:nn { \l__luamml_flag_int } { 8 } } }
396 {
397   \tag_struct_begin:n {tag=mtext,stash}
398   \int_set:Nn \l__luamml_amsmath_tag_struct_num_int { \tag_get:n {struct_num} }
399 }
400 \tag_struct_begin:n {tag=Lbl}
401 \tag_mc_begin:n {}
402 }
403 \AssignSocketPlug{tagsupport/math/display/tag/begin}{luamml}
404 \NewSocketPlug{tagsupport/math/display/tag/end}{luamml}
405 {
406   \tag_mc_end:
407   \tag_struct_end:
408   \bool_lazy_and:nnT
409   { \tl_if_exist_p:c { c__luamml_label_ \@currentenv _tl } }
410   { \int_if_odd_p:n { \int_div_truncate:nn { \l__luamml_flag_int } { 8 } } }
411   {
412     \tag_struct_end:
413   }
414   \tag_mc_begin:n {}
415 }
416 \AssignSocketPlug{tagsupport/math/display/tag/end}{luamml}
417 </luatex>

```

B.8.6 Horizontal boxes

This socket annotates an `\hbox` inside box commands used in math. We test for the socket until the release 2025-06-01.

```

418 \str_if_exist:cF { l__socket_tagsupport/math/luamml/hbox_plug_str }
419 {
420   \NewSocket{tagsupport/math/luamml/hbox}{2}
421   \NewSocketPlug{tagsupport/math/luamml/hbox}{default}{#2}
422   \AssignSocketPlug{tagsupport/math/luamml/hbox}{default}
423 }
424 <*\luatex>
425 \NewSocketPlug{tagsupport/math/luamml/hbox}{luamml}
426 {
427   \bool_lazy_and:nnTF
428   { \mode_if_math_p: }
429   { \int_if_odd_p:n { \int_div_truncate:nn { \l__luamml_flag_int } { 8 } } }
430   {
431     \tag_struct_begin:n
432     {
433       tag=mtext,
434       stash,
435     }
436     \tag_mc_begin:n {}
437     \luamml_annotate:en
438     {
439       nucleus = true,
440       structnum=\tag_get:n{struct_num}
441     }
442     { #2 }
443     \tag_mc_end:

```



```

444     \tag_struct_end:
445     }
446     { #2 }
447   }
448 \AssignSocketPlug{tagssupport/math/luamml/hbox}{luamml}
449 \</luatex>

```

B.8.7 Artifact characters

Unicode characters like a root sign should be marked as artifacts to avoid duplication e.g. in derivation if mathml structure elements are used that imply the meaning. We test for the socket until the release 2025-06-01.

```

450 \str_if_exist:cF { l__socket_tagssupport/math/luamml/artifact_plug_str }
451 {
452   \NewSocket{tagssupport/math/luamml/artifact}{0}
453 }
454 \<luatex>
455 \NewSocketPlug{tagssupport/math/luamml/artifact}{luamml}
456 {
457   \int_if_odd:nT { \int_div_truncate:nn { \l__luamml_flag_int } { 8 } }
458   {
459     \tag_mc_begin:n{artifact}
460   }
461 }
462 \AssignSocketPlug{tagssupport/math/luamml/artifact}{luamml}
463 \</luatex>

```

B.8.8 Math phantom socket

This socket is used around `\finph@nt`. It should be provided until 2025-06-01

```

464 \str_if_exist:cF { l__socket_tagssupport/math/luamml/finph@nt_plug_str }
465 {
466   \NewSocket{tagssupport/math/luamml/finph@nt}{2}
467   \NewSocketPlug{tagssupport/math/luamml/finph@nt}{default}{#2}
468   \AssignSocketPlug{tagssupport/math/luamml/finph@nt}{default}
469 }
470 \<luatex>
471 \NewSocketPlug{tagssupport/math/luamml/finph@nt}{luamml}
472 {
473   \luamml_annotate:nen {1}
474   {
475     nucleus = true,
476     mathml =
477     {
478       [0] = 'mpadded',
479       \ifh@else
480         width = 0,
481       \fi
482       \ifv@else
483         height = 0, depth = 0,
484       \fi
485       consume_label'mathphant',
486     },

```

```

487     }
488     { #2 }
489   }
490   \AssignSocketPlug{tagsupport/math/luamml/finph@nt}{luamml}
491 </luatex>

```

B.8.9 Math smash socket

This socket is used around `\finsm@sh`. It should be provided until 2025-06-01

```

492 \str_if_exist:cF { l__socket_tagsupport/math/luamml/finsm@sh_plug_str }
493 {
494   \NewSocket{tagsupport/math/luamml/finsm@sh}{2}
495   \NewSocketPlug{tagsupport/math/luamml/finsm@sh}{default}{#2}
496   \AssignSocketPlug{tagsupport/math/luamml/finsm@sh}{default}
497 }
498 <*luatex>
499 \NewSocketPlug{tagsupport/math/luamml/finsm@sh}{luamml}
500 {
501   \luamml_annotate:nen {2}
502   {
503     nucleus = true,
504     mathml = consume_label('mathsmash',
505       function(padded, core)
506         padded.height, padded.depth = 0, 0~
507         return~padded, core~
508       end),
509   }
510   { #2 }
511 }
512 \AssignSocketPlug{tagsupport/math/luamml/finsm@sh}{luamml}
513 </luatex>

```

B.9 Patching

For some packages, we ship with patches to make them more compatible and to demonstrate how other code can be patched to work with `luamml`.

These are either loaded directly if the packages are loaded or delayed using \LaTeX 's hook system otherwise.

`__luamml_patch_package:nn` For this, we use two helpers: First a wrapper which runs arbitrary code either now (if the package is already loaded) or as soon as the package loads, second an application of the first one to load packages following `luamml`'s naming scheme for these patch packages.

```

514 \cs_new_protected:Npn __luamml_patch_package:nn #1 #2 {
515   \@ifpackageloaded {#1} {#2} {
516     \hook_gput_code:nnn {package/#1/after} {luamml} {#2}
517   }
518 }
519 \cs_new_protected:Npn __luamml_patch_package:n #1 {
520   __luamml_patch_package:nn {#1} {
521     \RequirePackage { luamml-patches-#1 }
522   }
523 }

```

(End of definition for `__luamml_patch_package:nn` and `__luamml_patch_package:n`.)

We currently provide minimal patching for the kernel, `amsmath`. Currently only the kernel code supports pdf \TeX , but it's planned to extend this.

```

524 \RequirePackage { luamml-patches-kernel }
525 <*luatex>
526 \__luamml_patch_package:n {amsmath}
527 </luatex>

```

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

A		G	
<code>\AddToHook</code>	264	group commands:	
<code>\AssignSocketPlug</code>	225,	<code>\group_begin:</code>	123, 134
	227, 233, 238, 243, 253, 261, 281,	<code>\group_end:</code>	128, 141
	282, 283, 284, 295, 309, 314, 319,	H	
	324, 331, 336, 343, 356, 361, 403,	<code>\hbox</code>	16
	416, 422, 448, 462, 468, 490, 496, 512	hook commands:	
B		<code>\hook_gput_code:nnn</code>	516
bool commands:		<code>\hook_new_with_args:nn</code>	23
<code>\bool_lazy_and:nnTF</code>	393, 408, 427	<code>\hook_use:nnw</code>	26
C		I	
clist commands:		int commands:	
<code>\clist_map_inline:nn</code>	370	<code>\int_div_truncate:nn</code>	
cs commands:		38, 395, 410, 429, 457
<code>\cs_generate_variant:Nn</code>	144	<code>\int_eval:n</code>	157
<code>\cs_if_exist:NTF</code>	119	<code>\int_gincr:N</code>	147, 165, 197
<code>\cs_new:Npn</code>	35, 42	<code>\int_if_odd:nTF</code>	457
<code>\cs_new_eq:NN</code>	214	<code>\int_if_odd_p:n</code>	395, 410, 429
<code>\cs_new_protected:Npn</code> .	25, 30, 55,	<code>\int_mod:nn</code>	37
	59, 63, 68, 77, 82, 89, 95, 101, 106,	<code>\int_new:N</code> ...	10, 11, 16, 17, 145, 351
	112, 122, 133, 146, 164, 196, 514, 519	<code>\int_set:Nn</code>	
<code>\cs_set_eq:NN</code>	19, 32, 57, 61, 65, 70, 78, 84,
... 34, 73, 74, 75, 76, 80, 86, 131, 132			124, 125, 135, 136, 137, 138, 140, 398
D		<code>\int_use:N</code>	150, 155,
<code>\directlua</code>	5		168, 173, 175, 183, 189, 200, 202, 218
<code>\displaystyle</code>	6, 46	<code>\c_max_int</code>	124, 125, 137, 138
E		<code>\l_tmpa_int</code>	135, 140
<code>\else</code>	479, 482	Invalid commands:	
<code>\endarray</code>	12	<code>\Invalid_mathstyle</code>	51
exp commands:		iow commands:	
<code>\exp_not:n</code>	186	<code>\iow_new:N</code>	120
F		<code>\iow_newline:</code>	159, 177
<code>\fi</code>	481, 484	<code>\iow_now:Nn</code>	
		153, 171, 181, 187, 198, 209, 217
		<code>\iow_open:Nn</code>	121
		<code>\iow_shipout_x:Nn</code>	148, 166
		<code>\c_log_iow</code>	131

J	
<code>\jobname</code>	121
L	
lua commands:	
<code>\lua_now:n</code>	21, 264
luamml commands:	
<code>\luamml_annotate:nn</code>	95, 101, 144, 164, 248, 437
<code>luamml_annotate:nn</code>	1
<code>\luamml_annotate:nnn</code>	95, 95, 144, 146, 473, 501
<code>\luamml_attribute:nnn</code>	106, 106
<code>\luamml_attribute_core:nnn</code>	106, 112
<code>\luamml_begin_single_file:</code> ...	8, 93
<code>luamml_begin_single_file:</code>	1
<code>\luamml_end_single_file:</code>	93
<code>luamml_end_single_file:</code>	1
<code>\luamml_flag_ignore:</code>	80
<code>\luamml_flag_process:</code>	34
<code>\luamml_flag_save:n</code>	73
<code>\luamml_flag_save:nN</code>	74
<code>\luamml_flag_save:nn</code>	75
<code>\luamml_flag_save:nNn</code>	76
<code>\luamml_flag_structelem:</code>	86
<code>\luamml_get_last_mathml_stream:n</code> ..	5
<code>\luamml_ignore:</code>	77, 77, 80
<code>\luamml_pdf_write:</code>	195, 196, 214
<code>\luamml_process:</code>	7, 30, 30, 34, 93
<code>\luamml_register_output_hook:N</code> ...	5
<code>\luamml_save:</code>	6
<code>\luamml_save:...</code>	11
<code>\luamml_save:n</code>	55, 55, 73
<code>\luamml_save:nN</code>	55, 59, 74
<code>\luamml_save:nn</code>	55, 63, 75, 236
<code>\luamml_save:nNn</code>	55, 68, 76, 231
<code>\luamml_set_filename:n</code>	88, 89
<code>luamml_set_filename:n</code>	1
<code>\luamml_structelem:</code> ...	7, 81, 82, 86
luamml internal commands:	
<code>__luamml_amsmath_finalize_-</code> <code>inner_table:</code>	317
<code>__luamml_amsmath_finalize_-</code> <code>table:n</code>	329
<code>__luamml_amsmath_save_inner_-</code> <code>table:n</code>	307
<code>__luamml_amsmath_save_smallmatrix:</code>	312
<code>__luamml_amsmath_save_tag_with_-</code> <code>struct_elem:N</code>	354
<code>__luamml_amsmath_set_row_-</code> <code>columnalign:n</code>	341
<code>__luamml_amsmath_set_tag:</code>	359
<code>\l__luamml_amsmath_tag_struct_-</code> <code>num_int</code>	351, 354, 398
<code>__luamml_annotate_attribute_-</code> <code>end:wee</code>	109, 115
<code>__luamml_annotate_begin:</code>	96, 102, 107, 113
<code>__luamml_annotate_end:n</code>	104
<code>__luamml_annotate_end:we</code>	98
<code>\g__luamml_annotation_id_int</code> ...	145, 147, 150, 155, 165, 168, 173, 175, 183, 189
<code>__luamml_array_finalize_array:</code>	271
<code>__luamml_array_finalize_col:w</code> ..	279
<code>__luamml_array_init_col:</code>	275
<code>__luamml_array_save_array:</code>	267
<code>\l__luamml_filename_tl</code>	12, 90
<code>\l__luamml_flag_int</code>	10, 32, 38, 57, 61, 65, 70, 78, 84, 202, 395, 410, 429, 457
<code>\g__luamml_formula_id_int</code> ..	16, 197, 200
<code>\l__luamml_label_tl</code>	15, 31, 56, 60, 64, 69, 83, 206
<code>__luamml_maybe_structelem:</code>	35, 35, 57, 61, 65, 70
<code>__luamml_output_hook:n</code>	25, 28
<code>__luamml_patch_package:n</code>	514, 519, 526
<code>__luamml_patch_package:nn</code>	514, 514, 520
<code>__luamml_pdf_set_showstream:</code> ..	132
<code>__luamml_pdf_showlists:</code>	119, 122, 133, 185, 191, 208
<code>\l__luamml_pdf_stream</code>	120, 121, 126, 131, 148, 153, 166, 171, 181, 187, 198, 209, 217
<code>\l__luamml_pretty_int</code>	11, 19
<code>__luamml_register_output_hook:N</code>	28
<code>\l__luamml_root_tl</code>	13, 14, 66, 71, 204
<code>__luamml_style_to_num:N</code>	42, 42, 61, 70
M	
mode commands:	
<code>\mode_if_math:TF</code>	271
<code>\mode_if_math_p:</code>	428
N	
<code>\NewDocumentCommand</code>	216
<code>\NewSocket</code>	224, 226, 241, 257, 258, 259, 260, 288, 300, 301, 302, 323, 335, 347, 348, 366, 367, 420, 452, 466, 494
<code>\NewSocketPlug</code>	229, 234, 242, 246, 265, 269, 273, 277, 291, 305, 310, 315, 327, 339, 352, 357, 390, 404, 421, 425, 455, 467, 471, 495, 499

P	
Plugs:	tagsupport/math/luamml/array/finalizecol (plug) 277
tagsupport/math/luamml/array/finalize	tagsupport/math/luamml/array/initcol (plug) 273
tagsupport/math/luamml/array/finalizecol	tagsupport/math/luamml/array/save (plug) 265
tagsupport/math/luamml/array/initcol	TeX and L ^A T _E X 2 _ε commands:
tagsupport/math/luamml/array/save	\@classz 13
\ProvidesExplPackage 3, 7	\@currenvir 307, 394, 409
R	
\RegisterFamilyMapping 215	\@ifpackageloaded 515
\RequirePackage 521, 524	\finph@nt 17
S	
scan commands:	\finsm@sh 18
\scan_stop: 20, 98, 132, 214	\ifh@ 479
\scriptscriptstyle 49	\ifv@ 482
\scriptstyle 48	tex commands:
\showlists 9	\tex_interactionmode:D . 135, 136, 140
\showstream 119, 126	\tex_mathflattenmode:D 20
str commands:	\tex_numexpr:D 98
\str_if_exist:NTF 222, 239, 255, 286, 298,	\tex_showboxbreadth:D 125, 138
321, 333, 345, 364, 418, 450, 464, 492	\tex_showboxdepth:D 124, 137
T	
tag commands:	\tex_showlists:D 127, 139
\tag_get:n 398, 440	\textstyle 6, 47
\tag_mc_begin:n ... 401, 414, 436, 459	tl commands:
\tag_mc_end: 392, 406, 443	\tl_const:Nn 389
\tag_struct_begin:n 397, 400, 431	\tl_if_exist_p:N 394, 409
\tag_struct_end: 407, 412, 444	\tl_new:N 12, 13, 15
tagsupport/math/luamml/array/finalize	\tl_set:Nn 14, 31, 56, 60, 64, 66, 69, 71, 83, 90
(plug) 269	\tl_to_str:n 144
U	
use commands:	token commands:
\use:N 293	\token_case_meaning:NnTF 45
\use:n 180	\tracingmathml 5, 17
\UseExpandableTaggingSocket 14	